

INLINE GRINDER PUMP SYSTEM



- 40 HP MOTOR WITH OPTIONAL FREQUENCY CONTROLLER FOR EXACT KNIFE RPM SETTINGS
- FAN COOLED INDUSTRIAL GEARBOX
- 4 TPI ACME THREADS • STANDARD 11" CUTTING PARTS
- 4" INLET CAN BE POSITIONED AT 30 DEGREE INTERVALS
- AVAILABLE IN SINGLE PLATE, DOUBLE PLATE, OR TRIPLE PLATE CONFIGURATIONS
- AVAILABLE WITH EXCLUSIVE BCA-2 BONE COLLECTION ASSEMBLY
- NUMEROUS CONFIGURATIONS CAN BE SET-UP TO GRIND A VARIETY OF PRODUCTS INCLUDING PORK, BEEF, CHICKEN, & PET FOOD
- CAN BE EQUIPPED WITH A TRANSITION FUNNEL TO FEED PRODUCT TO ANOTHER MACHINE VIA PIPE CONNECTION
- DESIGNED & MANUFACTURED WITH DURABILITY & LONGEVITY IN MIND
- TWIN INTERMESHING FEED SCREWS • 500-10,000 LB. CAPACITY HOPPER
- VARIABLE SPEED POSITIVE DISPLACEMENT PUMP • HOPPER GRATE WITH SAFETY SWITCHES
- VARIABLE SPEED AUGER AGITATOR TO PREVENT BRIDGING
- CUSTOM BUILT TO YOUR SPECIFICATIONS

FPEC.COM

ARKANSAS
479.751.9392



SALES@FPEC.COM

CALIFORNIA
562.802.3727